

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47L 9/00, 9/22	A1	(11) International Publication Number: WO 95/13736 (43) International Publication Date: 26 May 1995 (26.05.95)
(21) International Application Number: PCT/GB94/02515 (22) International Filing Date: 15 November 1994 (15.11.94) (30) Priority Data: 9323784.0 18 November 1993 (18.11.93) GB (71) Applicant (for all designated States except US): NUMATIC INTERNATIONAL LIMITED [GB/GB]; 2 Knoll Road, Camberley, Surrey GU15 3SY (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): DUNCAN, Christopher, Robert [GB/GB]; Chilworthy House, Chilworthy, Chard, Somerset TA20 3BH (GB). GAILES, Michael, Edward [GB/GB]; 2 Paulet Close, Hook, Beaminstor, Dorset DT3 3PB (GB). (74) Agents: EVANS, David, Charles et al.; F.J. Cleveland & Co., 40-43 Chancery Lane, London WC2A 1JQ (GB).		(81) Designated States: AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KE, KG, KP, KR, KZ, LK, LT, LU, LV, MD, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TJ, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: VACUUM CLEANERS (57) Abstract Vacuum cleaning apparatus having air flow generating means to generate an airflow from a nozzle means to a receptacle to entrain dirt and debris and to transport said dirt and debris to the receptacle for collection and ultimate disposal, in which the air flow generating means is a fan driven by electric motor which latter is rated to produce a fan rotation speed greater than 24,000 rpm and a fully open air flow of greater than 3 m ³ . In a particular aspect of the invention the effect is to use a smaller motor and make it work much harder and faster in order to achieve a given air flow performance and then providing corresponding insulation around the motor to reduce the noise therefrom to below 50 dba.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

VACUUM CLEANERS

DESCRIPTION

5 This invention relates to vacuum cleaning apparatus and has particular reference to vacuum cleaning apparatus of the cannister or cylinder type. Such vacuum cleaning apparatus comprises in general a receptacle for the collection of dirt and debris,
10 inlet means for the admission of dirt and debris to said receptacle, collection means in operative connection with said inlet means for collection of said dirt and debris, air flow generating means to generate an air flow, from said collectiong means to
15 said receptacle, to entrain dirt and debris and to transport said dirt and debris to said receptacle for collection therein and ultimate disposal. Such apparatus is generally well known and will be referred to hereafter as "apparatus of the kind described".

20 Such apparatus of the kind described operates by generating an air flow over a surface or object to be cleaned, the air flow being such that particles of dirt, dust and debris are dislodged from the surface

- 2 -

upon which they reside and are entrained in the air flow and are carried by the air stream to the collection receptacle. As the air flow enters the collection receptacle the increased space within which the air flow can move results in a slowing down of the air with the result that the dirt, dust and debris are deposited within the receptacle. In typical vacuum cleaning apparatus currently available, the air flow generating means is a fan driven by an electric motor.

5 The fan may be a displacement fan and/or a centrifugal fan and in order to obtain satisfactory performance a motor rating of something of the order of 1000 W is necessary with an air flow of the order of 2.5 cu.metres per minute. The amount of air flow

10 depends, of course, on the diameter of the connection between the collection means and the inlet means to the dirt or debris collection receptacle; in general the larger the diameter of the connecting means, the greater needs to be the volume of the air flow to

15 provide the necessary velocity to maintain the dirt, dust and debris in entrainment within the air flow for transport to the receptacle for subsequent deposit therein.

20

- 3 -

Current motors operate at a rating of 1000 W with a spindle velocity of 19000 to 23000 rpm. Such motors are typically insulated by a layer of thick wool lagging around the outer casing of the motor and such
5 a machine will typically generate a noise output of the order of 58 dba.

Numerous attempts have been made to reduce the noise of vacuum cleaning apparatus. Some reduction can be
10 effected by including more sound insulation material around the motor. This can reduce the sound output by up to 3 dba but, in some designs of cleaner, this presents an increasing problem in terms of cooling of the motor.

15

Many attempts have been made to decrease the noise output of vacuum cleaners while maintaining their cleaning effectiveness by increasing the size of the
20 motor and having it work at a slower speed and/or in a less stressed manner. This has the disadvantage that an increase in fan size is necessary in order to obtain the same volumetric air displacement. The advantage of this arrangement is that the motor exerts

- 4 -

more power and in the fully blanked off condition,
a pressure decrease of 2500 mm of water gauge or
more can be obtained. The disadvantage of this
arrangement is, of course, the increase in size and
5 bulk of the components concerned. This in turn allows
for less free space within in any given motor housing
to accommodate sound insulation material.

The present applicants have, contrary to established
10 practice in the industry, sought to deal with the
problem by providing in one aspect of their invention
vacuum cleaning apparatus of the kind described in
which the air flow generating means is a fan driven by
an electric motor which motor is rated to produce a
15 fan rotation speed greater than 24000 rpm and a fully
open air flow of greater than 3 cu.metres per minute.

The applicants have found, surprisingly, that by using
a smaller electric motor and running it at a higher
20 speed, they are able to incorporate an increased
amount of sound insulation in juxtaposition the motor
and reduce the noise therefrom to below 50 dba.

- 5 -

In a particular aspect of the present invention the air flow may be 3.3 cu.metres per minute and the noise level may be reduced to below 47 dba.

5 The applicants have found that in spite of the use of a smaller motor and higher operating speeds they are still able to obtain, in the fully blanked off condition, a suction within the range of 2000 to 2400 mm water gauge.

10 The fan may be a displacement fan or is preferably a centrifugal fan. In a particular aspect of the invention, the fan is a centrifugal fan having a plurality of blades, each of which has a longer
15 leading edge at the air intake than trailing edge at the exhaust. In a further aspect of the invention, the length of the leading edge of each blade exceeds the length of the trailing edge by a ratio of at least 1.7:1.

20 In a typical embodiment of the invention, the motor is mounted on soft gasket means within a motor housing. This serves to insulate the motor from direct contact with the housing of the vacuum cleaning apparatus so

- 6 -

as to reduce the transmission of vibration from the motor to the surroundings. The housing surrounding the motor and fan may accommodate a plurality of layers of noise reduction material. The said layers
5 may be selected to filter out noise of different frequencies.

The motor may be a high speed motor which is small in size and light in weight and has, therefore, the
10 overall effect of reducing the lower frequency vibrations generated by the motor in use.

Following is a description by way of example only and with reference to the accompanying drawing of methods
15 of carrying the invention in to effect.

In the drawing:

The Figure is a section through the motor housing of a
20 cannister vacuum cleaner.

The housing indicated generally at (10) comprises a cylindrical body portion (11) having a substantially circular upper wall (12) and enclosed at its lower end

- 7 -

by a contoured motor supporting wall (13). The wall (13) is provided towards its centre with a substantially frustoconical dependant portion (14) having a further depending air inlet portion (15) is provided with a central opening to allow the ready ingress of air. The dependent portion (14) is provided with an annular, contoured rubber gasket (16) which serves as support for a motor and fan assembly indicated generally at (20). The motor assembly (20) comprises a motor body (21) having electrical connections (not shown) and a drive spindle connected to a fan (not shown) which latter is accommodated in a lower fan housing (22). Lower housing (22) is provided with a central bottom opening (23) for the admission of air which is drawn into the fan housing (22) and is expelled therefrom via the motor housing (21) as shown by the dark arrows in the accompanying drawing.

The motor and fan assembly (20) is secured in position by a clamping plate (27) which acts on a second annular contoured gasket (28) to secure the motor and fan assembly (21) in position. The motor and fan assembly

- 8 -

(21) is therefore secured to the housing (10) only through the means of the gaskets (16, 28).

5 The internal surface of the housing is provided with a first layer of sound insulation material (40) and internally of the housing there is also provided a substantially cylindrical internal wall comprising a series of layers (41, 42, 43 and 44) of insulation material. The space between the cylindrical wall (11)
10 and the internal wall formed by layers (41, 42, 43 and 44) defines an annular plenum chamber (30).

The upper portion of the inner cylindrical wall of insulation material is closed by means of circular
15 layers of insulation material (42, 43 and 44). Insulation material layers (43, 44) is of a foam rubber material and the remaining layers (40, 41, and 42) are selected each from a different material to damp out specific frequencies of sound generated by
20 the motor.

The cylindrical insulation layers (41, 42, 43 and 44) define a cage-like structure having a plurality of slots to permit air to pass from the area of the motor

- 9 -

housing (21) to the plenum chamber (30). The outer cylindrical housing (11) is also provided with a plurality of openings (48) to allow air to be exhausted to the atmosphere.

5

The apparatus described above has been found to provide a substantially reduced noise level. The motor has been found to be operable at speeds between 24000 and 30000 rpm with a motor rating of 1000W. The motor is smaller and lighter and the air flow can be increased to well above 3.0 cu.metres per minute. The fully blanked suction is still within the range 2000 to 2500 mm water gauge but is reduced when compared with prior art machines with the result when the nozzle is blocked with the machine still running, it is easier to remove the blockage.

10
15

It is well known that by using a smaller motor and making it run faster, the stress on the motor is substantially increased. By making it run faster, however, and reducing the motor and fan size and weight, the frequency of the generated noise is also significantly increased. The surprising feature of the invention is the fact that it is easier to absorb

20

- 10 -

the higher frequencies generated and since the motor
is smaller there is more room for sound insulation in
any given motor housing. Furthermore since the motor
itself is lighter there is less transmitted vibration
5 and the lighter motor is more readily cushioned on
rubber gaskets as illustrated above than would a more
powerful, heavier motor.


CLAIMS

1. Vacuum cleaning apparatus comprising a receptacle
for the collection of dirt and debris, inlet means
5 for the admission of dirt and debris to said
receptacle, nozzle means in operative connection
with said inlet means for the collection of dirt
and debris from a surface or area to be cleaned and
airflow generating means to generate an airflow
10 from said nozzle means to said receptacle to
entrain dirt and debris and to transport said dirt
and debris to said receptacle for collection
therein and ultimate disposal characterised in that
the said airflow generating means is a fan driven
15 by electric motor which motor is rated to produce a
fan rotation speed greater than 24000 rpm and a
fully open airflow of greater than 3 cu.m. pm.
2. Apparatus as claimed in claim 1 characterised by an
20 electric motor having sound insulation in
juxtaposition thereto to reduce the noise therefrom
to below 50 dba.
3. Apparatus as claimed in either of the preceeding
25 claims in which the open airflow is 3.3 cu.m. pm or
greater.

4. Apparatus as claimed in any preceeding claim characterised in that the audible noise level is below is 47 dba.
- 5 5. Apparatus as claimed in any preceeding claim characterised in that the motor has a fully blanked suction within the range of 2000 to 2500 mm water guage.
- 10 6. Apparatus as claimed in any preceeding claim characterised in that the fan is a displacement fan or a centrifugal fan.
- 15 7. Apparatus as claimed in claim 6 characterised in that the fan is a centrifugal fan having a plurality of blades, each blade of which has a longer leading edge at the intake than trailing edge at the exhaust.
- 20 8. Apparatus as claimed in any preceeding claim characterised in that the length of the leading edge of each blade exceeds the length of the trailing edge by a ratio of 1.7:1.
- 25 9. Apparatus as claimed in any preceeding claim characterised in that the electric motor is mounted on a soft gasket means within a motor housing.

10. Apparatus as claimed in any preceeding claim characterised in that the housing surrounding the motor and fan accomodates a plurality of layers of noise reduction material, said layers being
5 selected to filter out noise at different frequencies.
11. Apparatus as claimed in any preceeding claim characterised in that the insulation layers are
10 arranged to find a cage like structure having a plurality of slots to permit air to pass from the area of the motor housing to a plenum chamber.
12. Apparatus as claimed in any preceeding claim
15 characterised in that the motor has an operating speed of betwen 24000 and 30000 rpm with a motor rating of 1000 watt.

FIG. 1



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 94/02515

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 6 A47L9/00 A47L9/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 6 A47L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP,A,0 528 451 (DAEWOO ELECTRONICS CO LTD) 24 February 1993 see page 4, line 44 - page 11, line 4; figures	1,2,4,6, 10-12
Y	--- PATENT ABSTRACTS OF JAPAN vol. 9, no. 194 (M-403) 10 August 1985 & JP,A,60 060 300 (MATSUSHITA DENKI SANGYO KK) 6 April 1985 see abstract	1,2,4,6, 10-12
P,Y	--- WO,A,94 15519 (AB ELECTROLUX) 21 July 1994 see abstract --- -/--	1,6,10, 11

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

10 February 1995

Date of mailing of the international search report

17.02.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
 Fax (+ 31-70) 340-3016

Authorized officer

Vanmol, M

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 94/02515

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, Y	PATENT ABSTRACTS OF JAPAN vol. 18, no. 256 (P-1738) 16 May 1994 & JP,A,06 035 478 (TOKYO ELECTRIC CO LTD) 10 February 1994 see abstract ---	1, 6, 10, 11
A	PATENT ABSTRACTS OF JAPAN vol. 16, no. 253 (M-1263) 9 June 1992 & JP,A,04 060 199 (MATSUSHITA ELECTRIC IND CO LTD) 26 February 1992 see abstract ---	6-8
A	PATENT ABSTRACTS OF JAPAN vol. 13, no. 582 (M-911) 21 December 1989 & JP,A,88 070 009 (MATSUSHITA ELECTRIC IND CO LTD) 28 September 1989 see abstract -----	1, 9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 94/02515

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0528451	24-02-93	NONE	
WO-A-9415519	21-07-94	SE-B- 470563	29-08-94
		CN-A- 1093560	19-10-94
		FI-A- 940080	09-07-94
		NO-A- 940048	11-07-94
		SE-A- 9300033	09-07-94